CLAIMS

Claims 1-40 (Canceled)

Claim 41 (Currently Amended): A slicing machine for slicing food products [[(1)]], in particular blocks of sausage, meat or cheese, having <u>comprising</u> a rotating cutting blade [[(2)]], which is mounted so as to be displaceable parallel to its exist of rotation (3) a rotation axis of the cutting blade, characterised in that it comprises and a counterweight [[(4)]], which may be displaced is axially displaced in the opposite direction from the cutting blade [[(2)]].

Claim 42 (Canceled):

- Claim 43 (Currently Amended): [[A]] <u>The</u> slicing machine according to any one of the preceding of claim[[s]] <u>41</u>, characterised in that <u>wherein</u> displacement of the cutting blade, <u>(2) and/or of</u> the counterweight, <u>or both</u> [[(4)]] takes place independently of [[the]] <u>a</u> rotational speed of the cutting blade.
- Claim 44 (Currently Amended): [[A]] <u>The</u> slicing machine according to any one of the preceding of claim[[s]] 43, characterised in that the cutting blade <u>further</u> compris[[es]]ing a drive shaft [[(5)]], <u>wherein</u> and in that the cutting blade, (2) and/or the counterweight, or both (4) is(are) is mounted so as to be displaceable along the drive shaft [[(5)]].

Claim 45 - 49 (Canceled):

- Claim 50 (Currently Amended): A method for axial displacement of a cutting blade[[s]] during operation of a slicing machine, comprising the steps of axially displacing characterised in that a counterweight [[(4)]] on a drive shaft [[(5)]] of the cutting blade is-displaced in [[the]] an opposite direction from the cutting blade [[(2)]].
- Claim 51 (Currently Amended): [[A]] The method according to of claim 50, characteri[[s]]zed in that displacement wherein the displacing step, the displacement of the counterweight and the cutting blade are achieved is-

- Claim 52 (Currently Amended): [[A]] The method according to of claim 50, characterised in that wherein displacement of the cutting blade, (2) and of the counterweight, or both [[(4)]] is effected achieved by a spindle drive (6).
- Claim 53 (Currently Amended): A method of using at least one Use-of counterweight[[s]] in a slicing machine comprising the steps of (4)-displaceably axially displacing the at least one counterweight in the opposite direction from a cutting blade [[(2)]] to stabili[[s]]ze the running of the cutting blade [[(2)]] of [[a]] the slicing machine, which wherein the cutting blade includes an axis of rotation, and the cutting blade, the counterweight, or both is mounted so as to be displaceable parallel to [fits] the axis of rotation [f(3)].
- Claim 54 (Currently Amended): The method of Use according to claim 53, characterised in that wherein the step of axially displacing the at least one counterweight compensates for forces, and/or moments, or both arising during displacement of the blade are compensated.
- Claim 55 (Currently Amended): The method of claim 53 Use according to claim 13 or claim 14, characterised in that the further comprising the step of adjusting a zero point may be adjusted by axial displacement of the cutting blade [[(2)]] of [[a]] the slicing machine.
- Claim 56 (Currently Amended): The method Use according to claim 53, characterised in that the further comprising the step of measuring a torque produced by a of the drive of the cutting blade during is measured-during displacement thereof.

Claim 57 - 67 (Canceled):

- Claim 68 (Currently Amended): The slicing machine A device according to of claim 41, eharacterised in that wherein adjustment of [[the]] a cutting gap is effected when is achieved while the cutting blade is stationary or rotating.
- Claim 69 (Currently Amended): The slicing machine A device according to of claim 41, characterised in that the wherein an axial position of the cutting blade is not

<u>substantially</u> changed after [[it]] <u>the cutting blade</u> has come into contact with [[the]] an adjusting limit stop.

Claim 70 - 75 (Canceled):

- Claim 76 (New): The slicing machine of claim 41, wherein the counterweight is axially displaced relative to a feedback controlled drive shaft.
- Claim 77 (New): The slicing machine of claim 76, wherein the cutting blade is axially displaceable along the drive shaft in the same or opposite direction of the counterweight.
- Claim 78 (New): The slicing machine of claim 41, wherein the cutting blade is a circular blade, a helical blade, or a crescent shaped blade.
- Claim 79 (New): The slicing machine of claim 78, wherein the cutting blade is a crescent shaped blade.
- Claim 80 (New): The slicing machine of claim 78, wherein the displacement of the cutting blade, the counterweight, or both is achieved by a spindle arranged within the drive shaft, the spindle including a feedback-controlled drive that interacts with a thread of at least one sleeve, which is connected with the cutting blade, the counterweight, or both, for independent movement thereof.
- Claim 81 (New): The slicing machine of claim 41, wherein the displacement of the cutting blade, the counterweight, or both is achieved by a spindle arranged within the drive shaft, the spindle including a feedback-controlled drive that interacts with a thread of at least one sleeve, which is connected with the cutting blade, the counterweight, or both, for independent movement thereof.
- Claim 82 (New): The slicing machine of claim 78, wherein the drive shaft is driven by a toothed belt wheel, which interacts with the feedback-controlled drive; and wherein the counterweight is mounted non-rotationally, but axially displaceably on one or more bushes on the drive shaft, the drive shaft including a spindle, which is connected by way of a toothed belt wheel to the feedback-controlled drive.